

# PRODUCT DATA SHEET

## Ansell Lighting AAZLED200/ASY

### Aztec Asymmetrical Floodlight 200W

Manufacturer: Ansell Lighting

GTIN: 5056144246915

Family: Floodlighting

Range: Aztec Asymmetric



## DESCRIPTION

High performance die-cast aluminium LED floodlight suitable for industrial applications

- High output, high efficiency asymmetric lens technology for anti-light pollution
- Pre-installed breathable gland prevents internal moisture accumulation
- Bracket design allows installation without removing mounting bracket
- High efficiency up to 143 Lm/W
- Pre-wired with 1.5 metre of rubber insulated cable for ease of installation
- Non-dimmable

## TECHNICAL SPECIFICATION

**ETIM Class: Downlight / spot luminaire / floodlight (EC001744)**



### Primary Features

|                                  |             |                                             |           |
|----------------------------------|-------------|---------------------------------------------|-----------|
| Colour of light                  | White       | Luminaire efficacy (lm/W)                   | 141       |
| Colour temperature (K)           | 5000 - 5000 | Maximum system power (W)                    | 200       |
| Degree of protection (IP rating) | IP66        | Nominal voltage (V)                         | 230 - 230 |
| Lamp included                    | Yes         | Rated luminous flux acc. IEC 62722-2-1 (lm) | 28250     |



## Additional Features

|                                     |            |                                   |     |
|-------------------------------------|------------|-----------------------------------|-----|
| Adjustability                       | Swivelling | No dimming function               | Yes |
| Beam angle adjustable               | No         | Protection class                  | I   |
| Colour consistency (McAdam ellipse) | SDCM5      | Suitable for ceiling mounting     | No  |
| Colour rendering index (CRI/Ra)     | 70-79      | Suitable for light-track mounting | No  |
| Colour temperature switchable       | No         | Suitable for recessed mounting    | No  |
| Control gear included               | Yes        | Suitable for surface mounting     | Yes |
| Height/depth (mm)                   | 70         | Suitable for suspended mounting   | No  |
| Housing material                    | Aluminium  | Suitable for traverse mounting    | No  |
| Impact resistance (IK rating)       | IK08       | Suitable for wall mounting        | Yes |
| Length (mm)                         | 398        | Width (mm)                        | 300 |
| Light sharing                       | Asymmetric | With light sensor                 | No  |
| Lumen setting adjustable            | No         | With movement sensor              | No  |

## FURTHER DETAILS

Product Status (at download): Active

Date Updated: 03-05-2023

Trade Tariff Commodity Code: 9405423990

Country of Origin: CN

Ansell Lighting, Unit 6B Stonecross Industrial Park Yew Tree Way, Warrington, WA3 3JD

☎ 01942 433 333

✉ saleswarrington@anselluk.com

🌐 <http://www.anselluk.com>

## Disclaimer

- This Data Sheet was downloaded from EDATA - [www.edata.org.uk](http://www.edata.org.uk) - the UK electrotechnical industry data pool managed by EDA Data Services Limited on behalf of the Electrical Distributors' Association, on 16/10/2023.
- All intellectual property rights in the Product Data shown in this Data Sheet remains at all times the property of the Manufacturer named on the Data Sheet
- Product Data shown on the Data Sheet is for the product as supplied by the Manufacturer. Any subsequent modification of the product may affect specification and performance.
- Every reasonable effort is made to ensure accuracy of the Product Data which is believed to be correct at the date of download from EDATA. However neither the Manufacturer, the Wholesaler who downloaded the Data Sheet, nor EDA Data Services warrant the accuracy of the Product Data.
- The Product Data shown on the Data Sheet is not contractually binding. The Manufacturer reserves the right to amend the Product Data without prior notice.