

PRODUCT DATA SHEET

Ansell Lighting ALWP/1/MWS



Lynx Wallpack Microwave Sensor

Manufacturer: Ansell Lighting

GTIN: 5056144254026

Family: [Floodlighting]

Range: Lynx



DESCRIPTION

Robust wall mounted luminaire for general accent illumination with integral emergency option provides downward illumination with a beam angle of 60°. Power and CCT selectable; offering a choice of 2 outputs and 2 colour temperature options, in one luminaire.

- Robust wall mounted luminaire for general accent illumination and suitable for education, commercial, industrial applications
- Integral emergency option provides downward illumination with a beam angle of 60°
- Power and CCT selectable; offering a choice of 2 outputs and 2 colour temperature options, in one luminaire
- Die-cast aluminium body with vandal resistant polycarbonate Fresnel lens diffuser
- Tamper-proof allen key screws supplied as standard
- Multiple conduit entry and BESA box fixing points
- Photocell and sensor options

TECHNICAL SPECIFICATION



ETIM Class: Ceiling / wall luminaire (EC002892)

Primary Features

Colour of light	White	Light source type	LED replaceable
Housing colour	Black	Maximum system power (W)	30
Light source included	Yes	Voltage type	AC

Additional Features

Beam angle	Extreme wide beam >80°	Impact resistance (IK rating)	IK08
Beam angle adjustable	No	Length (mm)	300
Bluetooth operated	No	Light diffuser type	Diffuser
Colour consistency (McAdam ellipse)	SDCM6	Light distribution	Symmetric
Colour rendering index (CRI/Ra)	80-89	Light outlet	Direct
Colour temperature switchable	Discrete positions	Lumen maintenance at median useful life of 50,000 hrs at 25 °C ambient (tq) (%)	80
Compatible with Amazon Alexa	No	Lumen setting adjustable	No
Compatible with Apple HomeKit	No	Luminaire with limited surface temperature, class "D" in acc. with EN 60598-2-24	No
Compatible with Google Assistant	No	Power factor	85
Constant luminous flux control	No	Protection class according to IEC 61140	I
Control gear included	Yes	Rated life time L70/B50 at 25 °C (h)	54000
Cover material	Plastic opal	Replaceable control gear	Yes
Failure rate at median useful life of 50,000 hrs at 25 °C ambient (tq) (%)	50	Suitable for ceiling mounting	No
Fit for workplace acc. EN 12464-1	No	Suitable for surface mounting	Yes
Height/depth (mm)	50	Suitable for suspended mounting	No
Housing material	Plastic	Type of cabling	Suitable for through wiring
Housing surface protection	Plastic-coated	Width (mm)	50
IFTTT support available	No	With movement sensor	Yes

FURTHER DETAILS

Product Status (at download): Active

Date Updated: 15-07-2025

Trade Tariff Commodity Code: Not supplied

Country of Origin: CN

Ansell Lighting, Unit 6B Stonecross Industrial Park, Yew Tree Way, Warrington, WA3 3JD

☎ 01942 433 333

✉ saleswarrington@anselluk.com

🌐 <http://www.anselluk.com>

**Disclaimer**

- This Data Sheet was downloaded from EDATA - www.edata.org.uk - the UK electrotechnical industry data pool managed by EDA Data Services Limited on behalf of the Electrical Distributors' Association, on 14/10/2025.
- All intellectual property rights in the Product Data shown in this Data Sheet remains at all times the property of the Manufacturer named on the Data Sheet
- Product Data shown on the Data Sheet is for the product as supplied by the Manufacturer. Any subsequent modification of the product may affect specification and performance.
- Every reasonable effort is made to ensure accuracy of the Product Data which is believed to be correct at the date of download from EDATA. However neither the Manufacturer, the Wholesaler who downloaded the Data Sheet, nor EDA Data Services warrant the accuracy of the Product Data.
- The Product Data shown on the Data Sheet is not contractually binding. The Manufacturer reserves the right to amend the Product Data without prior notice.