


Pace 600x600



- Backlit LED panel suitable for education, commercial and ancillary area applications
- Slimline design allows for installation into shallow ceiling voids
- Integral switch allows the installer a choice of 3000K, 4000K and 6500K colour temperature
- Dimmable and OCTO options available
- TPa as standard
- **Switch Dim, DALI and 0-10V dimming capability using the multi dimmable driver accessories ADDIM/30/MC (see p199 for more information)**
- **Self-Test Panel Pod and Sensor Pod compatible (see p454 for more information)**



Powered by
CASAMBI



AIRMLED/POD/3NM/ST
Emergency Pod fitted

INPUT	HERTZ	TEMP	LIFETIME (HRS)	CRI	SDCM	BEAM ANGLE	CLASS	IP
220/240V	50/60Hz	-20°C to 40°C	L80 60,000	80	6	110°	2	IP40

CODE	DESCRIPTION	WATTAGE	CCT	LUMENS	LM/W	UGR
APAC2/60/1/CCT	600 x 600 - CCT Selectable	28W	3000K/4000K/6500K	3600lm (4000K)	120lm/W	21
APAC2/60/1/LO/CCT	600 x 600 - CCT Selectable - LO	23W		2500lm (4000K)	125lm/W	20

AIRMLED/POD/3NM/ST	Emergency Pod	5W
AIRMLED/POD/MWS	Sensor Pod	1W

* UGR Value based on (4H - 8H)

CODE (OPTIONS)	DESCRIPTION
/DM3	DALI Emergency
/OCTO	OCTO Smart Control

CODE (ACCESSORIES)	DESCRIPTION
APACLED/SK	Pace Suspension Kit
ASMF60/1	600x600 Surface Mounting Frame
APRK/60	600x600 Plasterboard Recessed Kit
AARX60K/1	600x600 Anti-Ligature Kit
ASRF/60/1	600x600 Skylight Recessed Frame
ADDIM/30/MC	30W Multi-current Dimmable LED Driver