

# PRODUCT DATA SHEET

## Ansell Lighting APRE6/1

### Proline Evo 1800mm CCT

Manufacturer: Ansell Lighting

GTIN: 5056144260584

Family: Commercial

Range: Proline Evo



## DESCRIPTION

Surface linear suitable for educational and commercial applications

- Modern contemporary fully enclosed high performance surface luminaire
- Steel powder coated body with reeded opal polycarbonate diffuser and retained end caps
- Low glare and uniform light distribution
- CCT selectable between 3000K and 4000K and power selectable; offering a choice of 2 outputs, in one luminaire
- Self-test emergency as standard
- Corridor Function for dimmable microwave sensor options
- Powered by Philips and Tridonic drivers

## TECHNICAL SPECIFICATION

**ETIM Class: Ceiling / wall luminaire (EC002892)**



### Primary Features

|                                  |             |                           |           |
|----------------------------------|-------------|---------------------------|-----------|
| Colour of light                  | White       | Lamp included             | Yes       |
| Colour temperature (K)           | 3000 - 4000 | Luminaire efficacy (lm/W) | 130       |
| Degree of protection (IP rating) | IP20        | Maximum system power (W)  | 53        |
| Housing colour                   | White       | Nominal voltage (V)       | 220 - 240 |



## Additional Features

|                                     |                        |                                 |     |
|-------------------------------------|------------------------|---------------------------------|-----|
| Beam angle                          | Extreme wide beam >80° | Suitable for ceiling mounting   | Yes |
| Colour consistency (McAdam ellipse) | SDCM6                  | Suitable for emergency lighting | No  |
| Colour rendering index (CRI/Ra)     | 80-89                  | Suitable for recessed mounting  | No  |
| Colour temperature switchable       | Discrete positions     | Suitable for surface mounting   | Yes |
| Height/depth (mm)                   | 73                     | Suitable for suspended mounting | No  |
| Housing material                    | Steel                  | Unified Glare Rating (UGR)      | 25  |
| Impact resistance (IK rating)       | IK06                   | Width (mm)                      | 148 |
| Protection class                    | I                      | With movement sensor            | No  |

## FURTHER DETAILS

Product Status (at download): Active

Date Updated: 16-05-2023

Trade Tariff Commodity Code: 9405119090

Country of Origin: CN

Ansell Lighting, Unit 6B Stonecross Industrial Park Yew Tree Way, Warrington, WA3 3JD

☎ 01942 433 333

✉ saleswarrington@anselluk.com

🌐 <http://www.anselluk.com>

### Disclaimer

- This Data Sheet was downloaded from EDATA - [www.edata.org.uk](http://www.edata.org.uk) - the UK electrotechnical industry data pool managed by EDA Data Services Limited on behalf of the Electrical Distributors' Association, on 18/10/2023.
- All intellectual property rights in the Product Data shown in this Data Sheet remains at all times the property of the Manufacturer named on the Data Sheet
- Product Data shown on the Data Sheet is for the product as supplied by the Manufacturer. Any subsequent modification of the product may affect specification and performance.
- Every reasonable effort is made to ensure accuracy of the Product Data which is believed to be correct at the date of download from EDATA. However neither the Manufacturer, the Wholesaler who downloaded the Data Sheet, nor EDA Data Services warrant the accuracy of the Product Data.
- The Product Data shown on the Data Sheet is not contractually binding. The Manufacturer reserves the right to amend the Product Data without prior notice.