



Prism Pro Anti Glare Fire Rated Downlight

Prism Pro CCT Anti Glare Fire Rated Downlight

Code: APRIPAG/1

Category	Downlights
Application	Ancillary, Hospitality, Residential, Retail
Specification	Architectural



PRODUCT FEATURES

- 220-240V IP65 LED dimmable CCT fire rated architectural downlight suitable for residential and hospitality applications
- Supplied with matt white bezel as standard. Chrome, satin chrome and matt black bezels sold separately
- New innovative 2 part detachable connector design allows initial wiring and testing to be completed first, then simply plug the downlight back to the connector, ensuring a quick and simple installation
- Low profile design and remote driver allow installation into shallow ceiling voids
- CCT selectable between 2700K, 3000K, 4000K and 6000K and power selectable; offering a choice of 2 outputs, in one luminaire
- Anti-glare design to create visual comfort
- Remote driver with 2x1.5mm + CPC loop-in, loop-out colour coded push fit piano terminals provide an easy and efficient installation
- Fully tested to meet Part C (moisture), Part E (acoustic) and Part L (energy) of Building Regulations

GENERAL INFORMATION

Wattage	5W - 7W
Lumens Delivered	450lm - 580lm (4000K)
Lm/W	90lm/W - 80lm/W (4000K)
Beam Angle	55
CRI	80
CCT	2700/3000/4000/6000K
Input	220/240V
Operating Temp	-20°C - 35°C
SDCM	6
UGR	20
Cut-Out Size	73mm
Energy efficiency class	E
Product Weight without Packaging	0.285 kg

TECHNICAL INFORMATION

Light Source	LED
Colour / Finish	White
Fire Rated	Yes
IP Rating	IP65
Class Protection	1
Internal / External	Internal
Surface / Recessed / Suspended	Recessed
Lumen Depreciation	L70 60,000h
Warranty (Years)	5
CE Mark	Yes
Diameter	88 mm
Height	85 mm

