

Vision 3 HP LED

Supplied c/w Integral Driver and 3 Trim Designs

- IP65 polycarbonate 3-In-1 LED luminaire for external applications
- Each fitting supplied with plain, louvred eyelid and plain eyelid covers
- Exceeds performance of CFL equivalents
- Four conduit entry points
- Integral die-cast aluminium heatsink provides thermally managed high performance
- 31W LED lifespan L70 36,000 hours




329



Removable conduit entry cap for ease of installation



Powered by
TRIDONIC
▼ enlightening your ideas



Fitted with Solid Eyelid



Fitted with Louvred Eyelid

LED Information

Total (Watts)	31W
Lumens Delivered	
31W	2426lm
Lm/W 31W	78lm*
CRI	Ra 80
CCT	4000K
Input	230V
Hertz	50/60Hz
Operating Temp	-10°C to 50°C

* Please note that Lm/W rating reduces for eyelid versions



Code	Lamp	Description
AVILED/HP/GR	LED	31W - Graphite - Cool White
AVILED/HP/SG	LED	31W - Silver Grey - Cool White
AVILED/HP/W	LED	31W - White - Cool White

Options	/PC	Electronic Photocell
	/M3	Emergency
	/DD	Digital Dimming (DD1/DD2/DD3/DD4)
	/MWS	Integral Microwave Sensor

Warrington: +44 (0) 1942 433333
Belfast: +44 (0) 2890 773750

