PRODUCT DATA SHEET

Ansell Lighting AZPLLED/2/M3

Z LED Linear 2 Emergency

Manufacturer: Ansell Lighting

GTIN: 5056144246984

Family: [Industrial]   Range: Z LED Linear

DESCRIPTION

Our Z LED Linear offers is a powerful and durable IP65 die-cast powder coated, 1-10Volt dimmable LED linear high bay with heatsink delivering optimum thermal transfer and performance. It also comes with a linkable bracket for continuous mounting making this ideal for industrial applications.

- Powerful and durable surface mounted IP65 linear high bay, perfect for the demands of industrial applications
- Surface mounting possible with AZPLLED/LC accessory
- 1.5m Suspension kit supplied as standard
- Die-cast aluminium construction provides enhanced thermal performance for longer LED lifespan
- Plug and play microwave sensor option, offering maximum energy saving
- 0/1-10V dimmable as standard (installer must drill through pilot hole and use an IP rated gland on install)

TECHNICAL SPECIFICATION

ETIM Class: High / low bay luminaire (EC001716)

Primary Features

Colour of light	White	Light source included	Yes
Colour temperature (K)	5000 - 5000	Maximum system power (W)	150
Degree of protection (IP rating)	IP65	Nominal voltage (V)	230 - 230

Additional Features

Beam angle	Extreme wide beam >80°	Housing material	Aluminium
Colour consistency (McAdam ellipse)	SDCM4	Impact resistance (IK rating)	IK08
Colour rendering index (CRI/Ra)	80-89	Length (mm)	890
Control gear included	Yes	Protection class according to IEC 61140	I
Dimming 0-10 V	Yes	Suitable for emergency lighting	Yes
Dimming 1-10 V	Yes	Width (mm)	147
Height/depth (mm)	134		

FURTHER DETAILS

Product Status (at download): Active

Date Updated: 15-07-2025

Trade Tariff Commodity Code: 9405119090

Country of Origin: CN

Ansell Lighting, Unit 6B Stonecross Industrial Park, Yew Tree Way, Warrington, WA3 3JD

☎ 01942 433 333   ✉ saleswarrington@anselluk.com   🖥 http://www.anselluk.com

Disclaimer