

Nylon Cable Ties



RoHS
Compliant



Standard Cable Ties

Suitable for a variety of applications, such as cable binding or harnessing

- Manufactured from UL approved virgin nylon 6/6
- General operating temperature: -40°C to 85°C
- Flammability rating: UL94V-2 (self-extinguishing within 30 seconds)
- UV resistant for outdoor use (black ties only)
- Black ties are halogen free
- RoHS compliant

Black and Natural Ties

Part No.	Size (mm)	Colour	Min. Tensile Strength (kg)
CT100-2.5N	100 x 2.5	Natural	8
CT100-2.5B	100 x 2.5	Black	8
CT160-2.5N	160 x 2.5	Natural	8
CT160-2.5B	160 x 2.5	Black	8
CT200-2.5N	200 x 2.5	Natural	8
CT200-2.5B	200 x 2.5	Black	8

Pack Quantity: 100

Part No.	Size (mm)	Colour	Min. Tensile Strength (kg)
CT100-2.5N/K	100 x 2.5	Natural	8
CT100-2.5B/K	100 x 2.5	Black	8

Pack Quantity: 1000

Part No.	Size (mm)	Colour	Min. Tensile Strength (kg)
CT140-3.6N	140 x 3.6	Natural	18
CT140-3.6B	140 x 3.6	Black	18
CT200-3.6N	200 x 3.6	Natural	18
CT200-3.6B	200 x 3.6	Black	18
CT300-3.6N	300 x 3.6	Natural	18
CT300-3.6B	300 x 3.6	Black	18

Pack Quantity: 100

Part No.	Size (mm)	Colour	Min. Tensile Strength (kg)
CT120-4.8N	120 x 4.8	Natural	22
CT120-4.8B	120 x 4.8	Black	22
CT160-4.8N	160 x 4.8	Natural	22
CT160-4.8B	160 x 4.8	Black	22
CT200-4.8N	200 x 4.8	Natural	22
CT200-4.8B	200 x 4.8	Black	22
CT250-4.8N	250 x 4.8	Natural	22
CT250-4.8B	250 x 4.8	Black	22
CT300-4.8N	300 x 4.8	Natural	22
CT300-4.8B	300 x 4.8	Black	22
CT370-4.8N	370 x 4.8	Natural	22
CT370-4.8B	370 x 4.8	Black	22
CT430-4.8N	430 x 4.8	Natural	22
CT430-4.8B	430 x 4.8	Black	22

Pack Quantity: 100

Colour Cable Ties

Part No.*	Size (mm)	Min. Tensile Strength (kg)
CT100-2.5	100 x 2.5	8
CT160-2.5	160 x 2.5	8
CT200-2.5	200 x 2.5	8
CT200-4.8	200 x 4.8	22
CT300-4.8	300 x 4.8	22

Pack Quantity: 100

*Please specify colour required - Red (red), Blue (blu), Yellow (yel), Green (gre), Orange (ora).
CT300-4.8 also available in silver (svr).