

Zip InLine ES



Zip InLine ES6 under-sink electronic instantaneous water heater single outlet for hand washing. Compact design, featuring bare-wire for fast heat up, no standing heat losses. Easy to install and service.



| MODEL | ENERGY CLASS (H/C) | MIN/MAX FLOW RATE | NOMINAL POWER RATING KW | DIMENSIONS W X D X H |
|-------|--------------------|-------------------|-------------------------|----------------------|
| ES6 | A | 1.5lpm / 3.3lpm | 5.5 kW @ 230V AC | 186mm x 87mm x 135mm |

Features and benefits

- Compact electronic instantaneous water heater with highly energy efficient bare wire system for economic water supply to a single outlet.
- The innovatively designed appliance heats the water automatically as it flows through, without wasting energy in standby operation.
- The heating power electronically compensates for variable inlet pressures and temperatures.
- Outlet temperature factory set to 38°C, but can be installer adjusted between 30°C to 43°C.
- Intended for use with taps having M22 /M24 nozzles.
- Easy to install and service.



Product detail

Specification type

| | |
|-------------------------|--------------------------------|
| Product code | ES6 |
| Product name | InLine ES6 Instantaneous 5.5kW |
| Energy efficiency class | A |
| Element type | Bare Wire Heating System |
| IP rating | 25 |

Capacity, weights & dimensions

| | |
|--------------------------------|----------------|
| Product weight | 1.3kg |
| Filled Product Weight | 1.5kg |
| Unit dimensions (W x D x H) mm | 186 x 87 x 135 |

Electrical

| | |
|-----------------------|------------------|
| Nominal power rating | 5.5 kW @ 230V AC |
| Nominal power supply | 230V |
| Nominal rated current | 24 amps |

Plumbing

| | |
|---|--|
| Wholesome water supply | Yes |
| Water connection Size | 1/2"BSP |
| Min water pressure | 0.65bar |
| Max water pressure | 10bar |
| Minimum flow rate l/pm | 1.5 |
| Maximum flow rate l/pm | 3.3 |
| Temperature increase at maximum flow rate | 26.2°C |
| Minimum water resistance @ 15oc | >800 |
| Installation - Plumbing (H/C) | The appliance is intended for connection to the wholesome water supply. It should be installed by a suitably qualified person. The appliance may be used as an unvented installation (as shown in the diagram opposite) or as a vented installation. |

The minimum water pressure will vary if a limescale filter is installed. Please contact us to discuss your requirements.

Typical Installation



