

LEDPRO10B

10W LED Professional Rewireable Floodlight - Black

Features & Benefits

- Fully polycarbonate front lens for enhanced light control, ideal for food preparation areas and grain stores
- Plug & Play PIR or Photocell option with linkable control (optional extra)
- Easy install bracket – enables floodlight fixing screws to be pre-fitted
- Durable powder coated finish
- IP65 weatherproof rating
- Adjustable mounting bracket with hook feature to enable easy assembly
- Driverless ACLED technology
- Rewireable with easy access screw terminals with link terminal for common accessories control
- Installer friendly captive terminal cover screws 2x PG11 glands supplied, suitable for 1.5mm twin and earth flat cable



Technical Data

Operating Voltage	230V AC
Frequency	50Hz
Installation Type	Bracket Mounted
Earth Class Rating	Class I
Operating Temperature	-20°C to 40°C
Ingress Protection Rating	IP65
Wattage	10
Beam Angle	113° x 108°

Data sheet

LEDPRO10B

Light / LEDPRO Lighting

Pan & Tilt Adjustment	360° (Tilt)
Energy Efficiency	Class F
Energy Usage	10kWh/1000H
Lumen Output (lm)	1160
Luminaire Efficiency	116 lm/W
Colour Temperature (K)	4000
LED Type	SMD (Integrated)
Mounting Hole Centres (mm)	98
Multiple Unit Support	Yes
Cable Capacity (mm ²)	1.5mm ² (Twin & Earth Cable)
Cable Entry(s)	Back Entry

General

Weight (g)	353
Height (mm)	110
Width (mm)	150
Depth (mm)	60
Body Construction	Polycarbonate (Body) Aluminium (Bracket)
Product Colour	Black
Accessories (Included)	Fittings (Rawl Plugs, Grommits, Screws)
Accessories (Optional)	LEDPROCAM, LEDPROPCB, LEDPROPCWH, LEDPROSLB, LEDPROSLWH, LEDPRORFKB, LEDPRORFKWH, LEDPROFOB
EAN Number	5012483013731
Guarantee Period	3 Years
Trade Tariff Commodity Code	9405114090

Data sheet

LEDPRO10B

Light / LEDPRO Lighting

Line Diagrams

