

Upgrade
May, 2025

Nimbo

Wattage & CCT switchable LED circular high bay with emergency option

Wattage switching CCT switching Built-in emergency UGR < 19 Flicker-free Ultra-high efficiency 

- High efficiency up to 140lm/W
- Switchable wattage and CCT (3000/4000K)
 - DALI dimming alternative driver available
 - Available in PC or aluminium shade
 - Die-cast aluminium
 - Vandal resistant (IK08)
 - Reflector included
- Low glare, UGR < 19* for 15W/25W outputs, UGR < 22 for 40W/60W outputs

Up to
140 $\frac{\text{lm}}{\text{W}}$

◀ NIM60

Order Code	Default Power	Alternative Power	Beam Angle	CCT	Lumen	Trade Price
NIM60 NIM60AL	-	15W	90°	Switchable**	1800lm(3000K) 1950lm(4000K)	£286.05 £289.10
	-	25W			3300lm(3000K) 3500lm(4000K)	
	-	40W			5200lm(3000K) 5600lm(4000K)	
	60W	-			7800lm(3000K) 8400lm(4000K)	

* UGR < 19 for room size of 4h x 2h, UGR < 21 for room size of 4h x 8h

** When CCT switchable, colour temperature switches between 3000K & 4000K

DALI

Order Code	Power	Beam Angle	CCT	Lumen	Trade Price
NIM60/DA	60W	90°	Switchable*	7800lm(3000K)	£333.74
NIM60AL/DA				8400lm(4000K)	£375.11

Emergency Option

Type	Description	Trade Price
/E	Emergency with LiFePO4 battery	See page 484-485

Accessory

Type	Order Code	Description	Trade Price
Suspension Kit	NIM-SUS	Maximum 1.0m drop	£18.97

- 7** Years Product Warranty
- 2** Years On-site Warranty
- 6000V** Surge Protection (L to GND)
- DALI** Dimmable Option



NIM60AL

Wattage Switch



CCT Switch

Suspension Kit
NIM-SUS

General Specification

Voltage	220-240Vac 50/60Hz
CRI	>80
SDCM	<5
L80B10 Lifetime	54000h
Power Factor	>0.9
Ambient Temp	-20°C to 50°C
Housing	Die-cast aluminium+PC



Order Code

NIM60-SCT
NIM60-SCT/DA
NIM60-SCT/E
NIM60AL-SCT
NIM60AL-SCT/DA
NIM60AL-SCT/E

Dimensions

